


C18 MALE CONNECTOR:




CONDUIT SIZE (mm)	THREAD TYPE	THREAD SIZE	ORDERING CODE	DIMENSIONS (mm)				
				THREAD DIA.	MIN. BORE	ACROSS FLATS	THREAD LENGTH	NOM LENGTH
16	Metric to BS 6053	16mm	BGM 0303	16.0	11.88	24.0	12.5	36.0
20		20mm	BGM 0404	20.0	13.88	28.0	14.0	39.0
25		25mm	BGM 0505	25.0	20.78	36.0	17.0	48.0
32		32mm	BGM 0606	32.0	25.88	46.0	19.0	57.0
40		40mm	BGM 0707	40.0	36.65	56.3	15.9	55.0
50		50mm	BGM 0808	50.0	45.35	65.5	22.2	70.0
63		63mm	BGM 0909	63.0	56.65	80.0	25.4	84.0

MATERIAL: BRASS TO BS2874

ORDERING CODE	NATO STOCK NUMBER
BGM0303	5975-99-888-8881
BGM0404	5975-99-593-8340
BGM0505	5975-99-016-0686
BGM0606	5975-99-127-4389
BGM0707	-
BGM0808	-
BGM0909	-

C18 FEMALE CONNECTOR:



CONDUIT SIZE (mm)	THREAD TYPE	THREAD SIZE	ORDERING CODE	DIMENSIONS (mm)				
				THREAD DIA.	MIN. BORE	ACROSS FLATS	THREAD LENGTH	NOM LENGTH
16	Metric to BS 6053	16mm	BTM 0303	16.0	14.0	24.0	13.0	36.0
20		20mm	BTM 0404	20.0	18.0	28.0	14.0	39.0
25		25mm	BTM 0505	25.0	23.0	36.0	17.0	48.0
32		32mm	BTM 0606	32.0	30.0	46.0	19.0	57.0
40		40mm	BTM 0707	40.0	38.0	56.3	22.4	55.0
50		50mm	BTM 0808	50.0	48.0	65.5	23.2	70.0
63		63mm	BTM 0909	63.0	61.0	80.0	25.5	84.0

MATERIAL: BRASS TO BS2874

ORDERING CODE	NATO STOCK NUMBER
BTM0303	5975-99-375-3248
BTM0404	5975-99-521-3508
BTM0505	5975-99-701-3495
BTM0606	5975-99-939-3051
BTM0707	-
BTM0808	-
BTM0909	-

PROPERTIES:

IP RATING WITH RECOMMENDED CONDUIT

IP 66 (NO INGRESS OF TALCUM POWDER UNDER VACUUM AND NO INGRESS OF WATER WITH NOZZLE SPRAY FROM 3m).

IP 67 (NO INGRESS OF TALCUM POWDER UNDER VACUUM AND NO INGRESS OF WATER AT 1m DEPTH FOR 30 MINUTES).

OPERATING TEMPERATURE

- 40 TO + 130° C. DEPENDING ON CONDUIT

FITTING INSTRUCTIONS INCLUDED WITH PRODUCT AND AVAILABLE ON REQUEST – LEAFLET No. 808869

The Company's policy is one of continuous improvement and reserves the right to change specifications at any time without prior notice.