

# Relay socket - PLC-BSC- 24DC/21-21 - 2967015

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



14 mm PLC basic terminal blocks with screw connection, 24 V DC input voltage (without relay or optocoupler)

Figure shows PLC-BSC-120UC/21-21/SO46 version



## Key commercial data

package_quantity	10
GTIN	4017918156459

## Technical data

### Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

### Dimensions

Width	14 mm
Height	80 mm
Depth	94 mm

### Ambient conditions

Ambient temperature (operation)	-40 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

### Input data

Nominal input voltage $U_N$	24 V DC
Status display	LED

### Output data

Compatible components	Miniature relay, REL-MR-24DC/21-21AU, REL-MR-24DC/21-21
-----------------------	---

### Connection data

Conductor cross section solid min.	0.14 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.14 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>

# Relay socket - PLC-BSC- 24DC/21-21 - 2967015

## Technical data

### Connection data

<b>Conductor cross section AWG/kcmil min.</b>	26
<b>Conductor cross section AWG/kcmil max</b>	14
<b>Connection method</b>	Screw connection
<b>Stripping length</b>	8 mm
<b>Screw thread</b>	M3

### General

<b>Color</b>	green
<b>Operating mode</b>	100% operating factor
<b>Inflammability class according to UL 94</b>	V0
<b>Mounting position</b>	any
<b>Assembly instructions</b>	In rows with zero spacing

## classifications

### eCl@ss

<b>eCl@ss 4.0</b>	27371102
<b>eCl@ss 4.1</b>	27371102
<b>eCl@ss 5.0</b>	27371603
<b>eCl@ss 5.1</b>	27371603
<b>eCl@ss 6.0</b>	27371603
<b>eCl@ss 7.0</b>	27371603
<b>eCl@ss 8.0</b>	27371603

### ETIM

<b>ETIM 2.0</b>	EC001456
<b>ETIM 3.0</b>	EC001456
<b>ETIM 4.0</b>	EC001456
<b>ETIM 5.0</b>	EC001456

### UNSPSC

<b>UNSPSC 6.01</b>	30211917
<b>UNSPSC 7.0901</b>	39121516
<b>UNSPSC 11</b>	39121516
<b>UNSPSC 12.01</b>	39121516
<b>UNSPSC 13.2</b>	39121516

## approvals

---


UL Recognized / cUL Recognized / GOST / GL / cULus Recognized /


---

### Approval details

## Relay socket - PLC-BSC- 24DC/21-21 - 2967015


### approvals

UL Recognized 

cUL Recognized 

GOST 

GL

cULus Recognized 

### Drawings

© Phoenix Contact 2014 - all rights reserved  
<http://www.phoenixcontact.com>