

Rittal – The System.

Faster – better – everywhere.

NH fuse-switch- disconnectors, size 00 to 3 – SV 9344.110

Date : Mar 18, 2014

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



NH fuse-switch-disconnectors, size 00 to 3 – SV 9344.110

created : 18.03.2014 on www.rittal.com/com-en



Product description

Material:

- Polyamide (PA 6)
- Fire protection corresponding to UL 94-V0
- Contact tracks: Electrolytic copper, silver-plated

Colour:

- Chassis: RAL 7035
- Cover: RAL 7035/7001

Basis of test:

- IEC/DIN EN 60 947-3
- DIN EN 60 269-2 (fuse inserts)

Note:

- The technical data may vary for RU applications. Applications to RU only in conjunction with "Special Purpose Fuses".

Packs of:

- 1 pc(s).

EAN:

- 4028177540606

Customs tariff number:

- 85365080

Product features

Design:

- 1

Number of poles:

- 3-pole

Dimensions:	• Width: 184 mm • Height: 298 mm
Type of electrical connection:	• Screw M10
Rated operating voltage:	• 690 V, 3~
Clamping area for laminated copper bars:	• Width: 32 mm • Height: 10 mm
Clamping area for round conductor cross-sections:	• 10 mm² - 150 mm² • fine wire with wire end ferrule: 10 mm² - 150 mm² • Solid: 10 mm² - 150 mm²
Rated operating current max.:	• 250 A
Cable outlet:	• Top/bottom
Approvals	
Approvals:	•  C-UR (EN) •  UR (EN)
Declarations:	•  Declaration of conformity (EN, DE)
Downloads	
Data sheets:	•  Technical details (EN)

Rittal – The System.

Faster – better – everywhere.

- Enclosures
- Power distribution
- Climate Control
- IT Infrastructure
- Software & services

Rittal GmbH & Co. KG
Postfach 1662 · D-35726 Herborn
Phone: +49 (0) 2772 505-0 · Fax: +49 (0) 2772 505-2319
E-Mail: info@rittal.com · www.rittal.com

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

