NSYS3D3315P

Spacial S3D plain door with mount.plate. H300xW300xD150 IP66 IK10 RAL7035.





Main

Range of product	Spacial S3D
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	300 mm
Enclosure nominal width	300 mm
Enclosure nominal depth	150 mm
Door type	Plain
Mounting plate description	Plain
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	Body 1 Mounting plate 1 Door with lock 1 Cable gland plate 1

Complementary

Variant particularity	Gutter-shaped front rail double sheet thickness Single piece body	
Number of doors	1 front face	
Door opening	Reversible 120 °	_
Lock type	3 mm double-bar lock	_
Accessibility for operation	Front	_
Removable parts	Door by hinges Cable gland plate by screws Mounting plate by fixing element	
Material	Galvanised steel for mounting plate Steel for enclosure	
Surface finish	Epoxy-polyester powder enclosure	
Colour	Grey RAL 7035 enclosure :	_
Standards	IEC 62208	
Product certifications	BV CUL DNV GL LR UL	

Environment

IP degree of protection	IP66 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0940 - Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Period 18 months

