NSYS3X6420

SPACIAL S3X stainless 304L, Scotch Brite® finish, H600xW400xD200 mm.





Main

Range of product	Spacial S3X
Device application	Multi-purpose
Product or component type	Compact enclosure
Enclosure nominal height	600 mm
Enclosure nominal width	400 mm
Enclosure nominal depth	200 mm
Installation accessory type	Wall-mounting
Device composition	1 body 1 door 2 perforated vertical profile drilled (door) 2 lock (door)

Complementary

Body type	Single piece body, cross-shaped structure Gutter shaped front rail	
Door type	Plain	
Number of doors	Front face: 1 door(s)	
Door opening	120°, reversible	
Lock type	2 points lock, 3 mm double-bar	_
Mounting plate description	Without mounting plate	_
Type of gland plate	Without gland plate	_
Accessibility for operation	Front	_
Removable parts	Door fixing: by hinges	_
Material	Body and door: stainless steel 304L Hinge: stainless steel Lock: zamak	
Surface finish	Lock: chromium plated Body and door: Scotch-Brite® brushed	
Thickness	1.5 mm	

Environment

Standards	IEC 62208	
Product certifications	CAN/CSA 22 UL 508 type A	
IP degree of protection	IP66 conforming to IEC 60529	
IK degree of protection	IK10 conforming to IEC 62262	
Environmental characteristic	Corrosive Specific hygiene	

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS	Compliant - since 0940 - Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	

Contractual warranty

Period 18 months

