



Main

Range of product	Canalis
Product name	KS
Product or component type	Tap-off unit
[Ie] rated operational current	20 A at 35 °C
Fuse type	BS88 - A1 - conforming to BS
Mounting mode	Plug-in
Tap-off unit polarity	3L+N+PE

Complementary

Device application	Medium power distribution
[Ue] rated operational voltage	230...690 V depending on protective device
[Uimp] rated impulse withstand voltage	6.8 kV
[Ui] rated insulation voltage	400 V depending on protective device 500 V depending on protective device 690 V depending on protective device
Network frequency	50/60 Hz
Protection type	Fuse
Electrical connection	Cable clamp terminal ISO32 6 mm² flexible Cable clamp terminal ISO32 10 mm² rigid
Tap-off unit disconnection mode	By drawing out
Tap-off unit connector type	With fixed polarity
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK08 conforming to IEC 62262
Provided equipment	Fuse not supplied
Standards	IEC 60439-2 IEC 61439-6
Colour	RAL 9001 white
Width	135 mm
Depth	103 mm
Height	165 mm
Product weight	0.6 kg

Environment

Earthing system	TT - busbar trunking TN-S - busbar trunking TN-C - busbar trunking IT - busbar trunking TT - tap-off unit TN-S - tap-off unit IT - tap-off unit
-----------------	---

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 1012 - Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

