170ENT11002

Modicon Momentum - Ethernet communication adaptor - 10 Mbit/s



Main

Range of product	Modicon Momentum automation platform
Product or component type	Ethernet TCP/IP communication adaptor
Communication port protocol	Ethernet TCP/IP
Method of access	Master/slave Peer to peer
Transmission rate	10 Mbit/s
Transmission support medium	Shielded twisted pairs cable

Complementary

Module configuration	BOOTP server to assign IP parameters	
Topology	Multidrop, star network	
Port Ethernet	10BASE-T	_
Number of devices	>= 0 with hub or repeater 032 per segment	_
Cable length	>= 1000 m with repeater 1000 m without repeater	
Addressing	IP address user assigned Unique IEEE global address	
Fail state	Fail safe	_
Control parameter	CRC-32	
Supply	From I/O base	_
Marking	CE	_
Local signalling	LED green Ethernet network state (LAN) LED green module active (RUN)	
Electrical connection	1 connector RJ45 for 10BASE-TX	
Product weight	0.07 kg	

Environment

Environment		
Product certifications	CSA FM Class 1 Division 2 UL	
Standards	CSA FM Class 1 Division 2	_
IP degree of protection	IP20	_
Protective treatment	TC	_
Resistance to electrostatic discharge	4 kV contact IEC 801-2 8 kV on air IEC 801-2	_
Resistance to electromagnetic fields	10 V/m 801000 MHz IEC 801-3	
Ambient air temperature for operation	060 °C	_
Ambient air temperature for storage	-4085 °C	_
Relative humidity	95 % without condensation	
Operating altitude	<= 5000 m	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 1015 - Schneider Electric declaration of conformity