


Pre-insulated Terminals



Ring Terminals

Material: Copper
Insulation: Polyvinyl Chloride
Max. elec. rating: ■ 19 amp
 ■ 27 amp
 ■ 48 amp
 600 volts 75°C


UL approval E100455
 CSA approval 093995
 RoHS compliant



Fork Terminals

Material: Copper
Insulation: Polyvinyl Chloride
Max. elec. rating: ■ 19 amp
 ■ 27 amp
 ■ 48 amp
 600 volts 75°C

UL approval E100455
 CSA approval 093995
 RoHS compliant



Vibration resistance - information available on request

Wire Range mm ² (AWG)	Part No.	Dimensions mm					
		D1	D3	D4	L	L1	D2
0.5-1.5 (22 - 16)	32RER	1.8	5.5	4.3	13.7	10	3.2
	37RER	1.8	6.6	4.3	15.5	10	3.7
	43RER	1.8	8.0	4.3	16.2	10	4.3
	53RER	1.8	8.0	4.3	16.7	10	5.3
	65RER	1.8	11.0	4.3	20.4	10	6.5
	85RER	1.8	12.0	4.3	20.2	10	8.5
1.5-2.5 (16 - 14)	10RER	1.8	14.5	4.3	25.1	10	10.0
	32BER	2.3	5.5	4.8	15.5	10	3.2
	37BER	2.3	6.6	4.8	15.6	10	3.7
	43BER	2.3	8.0	4.8	15.9	10	4.3
	53BER	2.3	8.0	4.8	16.9	10	5.3
	65BER	2.3	10.5	4.8	20.8	10	6.5
4-6 (12 - 10)	85BER	2.3	12.0	4.8	21.4	10	8.5
	10BER	2.3	14.5	4.8	23.6	10	10.0
	32YER	3.5	7.2	6.5	22.2	13.5	3.2
	37YER	3.5	7.2	6.5	22.2	13.5	3.7
	43YER	3.5	9.5	6.5	22.2	13.5	4.3
	53YER	3.5	9.5	6.5	22.2	13.5	5.3
4-6 (12 - 10)	65YER	3.5	11.0	6.5	23.5	13.5	6.5
	85YER	3.5	14.0	6.5	27.0	13.5	8.5
	10YER	3.5	15.0	6.5	30.0	13.5	10.0
	12YER	3.5	19.0	6.5	30.0	13.5	13.0

Pack Quantity: 100

Wire Range mm ² (AWG)	Part No.	Dimensions mm					
		D1	D3	D4	L	L1	D2
0.5-1.5 (22 - 16)	32RF	1.8	5.7	4.3	15.3	10	3.2
	37RF	1.8	6.4	4.3	15.3	10	3.7
	43RF	1.8	6.4	4.3	15.8	10	4.3
	53RF	1.8	7.5	4.3	16.4	10	5.3
	65RF	1.8	8.5	4.3	19.7	10	6.5
	1.5-2.5 (16 - 14)	32BF	2.3	6.0	4.8	16.0	10
37BF		2.3	6.4	4.8	15.7	10	3.7
43BF		2.3	6.4	4.8	16.1	10	4.3
53BF		2.3	8.5	4.8	16.2	10	5.3
4-6 (12 - 10)	65BF	2.3	11.0	4.8	20.1	10	6.5
	37YF	3.5	6.4	6.5	20.8	13.5	3.7
	43YF	3.5	7.1	6.5	21.0	13.5	4.3
	53YF	3.5	9.5	6.5	21.6	13.5	5.3
	65YF	3.5	12.0	6.5	24.9	13.5	6.5
	85YF	3.5	14.0	6.5	28.0	13.5	8.5
10YF	3.5	18.0	6.5	28.0	13.5	10.0	

Pack Quantity: 100

Non-insulated & Non-insulated High Temperature Terminals available on request.