




Through/Ground Conductor/Ex and Double-Potential Terminal Blocks 1 (1.5) mm², 2000 Series

0.14 - 1 (1.5) mm ² ① AWG 24 - 16 800 V/8 kV/3 ② 600 V, 10 A I _N 13.5 A (18 A) Terminal block width 3.5 mm / 0.138 in 9 - 11 mm / 0.39 in ③	0.14 - 1 (1.5) mm ² ① AWG 24 - 16 800 V/8 kV/3 ② 600 V, 10 A I _N 13.5 A (18 A) Terminal block width 3.5 mm / 0.138 in 9 - 11 mm / 0.39 in ③	0.14 - 1 (1.5) mm ² ① AWG 24 - 16 800 V/8 kV/3 ② 600 V, 10 A I _N 13.5 A (18 A) Terminal block width 3.5 mm / 0.138 in 9 - 11 mm / 0.39 in ③
---	---	---



Item No.	Pack. Unit	Item No.	Pack. Unit	Item No.	Pack. Unit
2-conductor through terminal block		3-conductor through terminal block		4-conductor through terminal block	
gray ⑤ 2000-1201 ⑤ 100		gray ⑤ 2000-1301 ⑤ 100		gray ⑤ 2000-1401 ⑤ 100	
blue ④ ⑤ 2000-1204 ④ ⑤ 100		blue ④ ⑤ 2000-1304 ④ ⑤ 100		blue ④ ⑤ 2000-1404 ④ ⑤ 100	
orange ⑤ 2000-1202 ⑤ 100		orange ⑤ 2000-1302 ⑤ 100		orange ⑤ 2000-1402 ⑤ 100	
red ⑤ 2000-1203 ⑤ 100		red ⑤ 2000-1303 ⑤ 100		red ⑤ 2000-1403 ⑤ 100	
black ⑤ 2000-1205 ⑤ 100		black ⑤ 2000-1305 ⑤ 100		black ⑤ 2000-1405 ⑤ 100	
yellow ⑤ 2000-1206 ⑤ 100		yellow ⑤ 2000-1306 ⑤ 100		yellow ⑤ 2000-1406 ⑤ 100	
2-conductor ground terminal block		3-conductor ground terminal block		4-conductor ground terminal block	
green-yellow ⑤ 2000-1207 ⑤ 100		green-yellow ⑤ 2000-1307 ⑤ 100		green-yellow ⑤ 2000-1407 ⑤ 100	
Item-Specific Accessories		Item-Specific Accessories		Item-Specific Accessories	
End and intermediate plate, 0.7 mm thick		End and intermediate plate, 0.7 mm thick		End and intermediate plate, 0.7 mm thick	
orange 2000-1292 100 (4x25)		orange 2000-1392 100 (4x25)		orange 2000-1492 100 (4x25)	
gray 2000-1291 100 (4x25)		gray 2000-1391 100 (4x25)		gray 2000-1491 100 (4x25)	

2000 Series Accessories

Appropriate marking systems: WMB/Marking strips
(see Section 13)

Push-in type jumper bar, insulated, I _N 14 A, light gray 2-way 2000-402 200 (8x25)	Delta jumper, insulated, ⑥ I _N = I _N terminal block, light gray 1-2 3-4 5-6 2000-406/020-000 100 (4x25)	Marking strip, plain, 11 mm wide, 50 m roll white 2009-110 1
3-way 2000-403 200 (8x25)	Star point jumper, insulated, ⑥ I _N = I _N terminal block, light gray 1-3-5 2000-405/011-000 100 (4x25)	WMB Multi marking system, 10 strips with 10 markers per card, for 3.5 mm terminal block width plain 793-3501 5
4-way 2000-404 200 (8x25)	Test plug adapter, for test plug 4 mm Ø gray 2009-174 100 (4x25)	
5-way 2000-405 100 (4x25)	Banana plug, ⑥ for socket 4 mm Ø, color mixed 215-111 50	
6-way 2000-406 100 (4x25)	Testing tap, for max. 2.5 mm ² gray 2009-182 100 (4x25)	
7-way 2000-407 100 (4x25)	Test plug, with 500 mm cable, 2 mm Ø red 210-136 50	
8-way 2000-408 100 (4x25)		
9-way 2000-409 100 (4x25)		
10-way 2000-410 100 (4x25)		
Push-in type jumper bar, insulated, I _N 14 A, light gray from 1 to 3 2000-433 200 (8x25)	Test plug, with 500 mm cable, 2.3 mm Ø yellow 210-137 50	
from 1 to 4 2000-434 200 (8x25)		
from 1 to 5 2000-435 100 (4x25)		
from 1 to 6 2000-436 100 (4x25)		
from 1 to 7 2000-437 100 (4x25)		
from 1 to 8 2000-438 100 (4x25)		
from 1 to 9 2000-439 100 (4x25)		
from 1 to 10 2000-440 100 (4x25)		
Protective warning marker, with high-voltage symbol, black, for 5 terminal blocks yellow 2000-115 100 (4x25)		

For list of approvals and user guide, see pages 634 to 637.