




TOPJOB® Double-Deck Terminal Blocks 1 (1.5) mm² 2000 Series




0.14 - 1 (1.5) mm² ① | AWG 24 - 16
500 V/6 kV/3 ②
I_N 13.5 A (18 A)
Terminal block width 3.5 mm / 0.138 in
③ 9 - 11 mm / 0.39 in ④

0.14 - 1 (1.5) mm² ① | AWG 24 - 16
500 V/6 kV/3 ②
I_N 13.5 A (18 A)
Terminal block width 3.5 mm / 0.138 in
③ 9 - 11 mm / 0.39 in ④

0.14 - 1 (1.5) mm² ① | AWG 24 - 16
500 V/6 kV/3 ②
I_N 13.5 A (18 A)
Terminal block width 3.5 mm / 0.138 in
③ 9 - 11 mm / 0.39 in ④



Item No.	Pack. Unit	Item No.	Pack. Unit	Item No.	Pack. Unit
Through/through terminal block, with marker carrier, gray housing		Through/through terminal block, with marker carrier, blue housing		Ground conductor/through terminal block, with marker carrier, gray housing	
● L/L	2000-2231 50	● N/N	2000-2234 50	● PE/N	2000-2247 50
● N/L	2000-2232 50			● PE/L	2000-2257 50
● L/N	2000-2233 50				
Through/through terminal block, without marker carrier, gray housing		Through/through terminal block, without marker carrier, blue housing		Ground conductor/through terminal block, without marker carrier, gray housing	
● L/L	2000-2201 50	● N/N	2000-2204 50	● PE/N	2000-2217 50
● N/L	2000-2202 50			● PE/L	2000-2227 50
● L/N	2000-2203 50				



Item No.	Pack. Unit	Item No.	Pack. Unit	Item No.	Pack. Unit
4-conductor through terminal block, with marker carrier, internal commoning, conductor entry position colored in violet, gray housing		4-conductor through terminal block, with marker carrier, internal commoning, conductor entry position colored in violet, blue housing		4-conductor ground terminal block, with marker carrier, internal commoning, green-yellow housing	
● L	2000-2238 50	● N	2000-2239 50	● PE	2000-2237 50
4-conductor through terminal block, without marker carrier, internal commoning, conductor entry position colored in violet, gray housing		4-conductor through terminal block, without marker carrier, internal commoning, conductor entry position colored in violet, blue housing		4-conductor ground terminal block, without marker carrier, internal commoning, green-yellow housing	
● L	2000-2208 50	● N	2000-2209 50	● PE	2000-2207 50

For list of approvals and user guide, see pages 634 to 637.