



Double-deck terminal block assembly

A double-deck marker carrier can be fitted retrospectively to double-deck terminal blocks without marker carrier.

① Conductor sizes: 0.14 mm² – 1.5 mm² "s + f-st";
Push-in conductor sizes: 0.5 mm² – 1.5 mm² "s"
and 0.5 mm² – 0.75 mm²
"insulated ferrule, 10 mm"

② 500 V = rated voltage
6 kV = rated surge voltage
3 = pollution degree
(see Section 14)

③ Strip length, see packaging or instructions.

2000 Series Accessories

Appropriate marking systems: WMB/Marking strips
(see Section 13)

End and intermediate plate, 0.7 mm thick	Test plug adapter,
orange 2000-2292 25	for test plug 4 mm Ø gray 2009-174 100 (4x25)
gray 2000-2291 25	
Push-in type jumper bar, insulated,	Banana plug,
I _N 14 A, light gray	for socket 4 mm Ø, color mixed 215-111 50
2-way 2000-402 200 (8x25)	
3-way 2000-403 200 (8x25)	
4-way 2000-404 200 (8x25)	
5-way 2000-405 100 (4x25)	
6-way 2000-406 100 (4x25)	
7-way 2000-407 100 (4x25)	
8-way 2000-408 100 (4x25)	
9-way 2000-409 100 (4x25)	
10-way 2000-410 100 (4x25)	
Push-in type jumper bar, insulated,	Testing tap,
I _N 14 A, light gray	for max. 2.5 mm ² gray 2009-182 100 (4x25)
from 1 to 3 2000-433 200 (8x25)	
from 1 to 4 2000-434 200 (8x25)	
from 1 to 5 2000-435 100 (4x25)	
from 1 to 6 2000-436 100 (4x25)	
from 1 to 7 2000-437 100 (4x25)	
from 1 to 8 2000-438 100 (4x25)	
from 1 to 9 2000-439 100 (4x25)	
from 1 to 10 2000-440 100 (4x25)	
Protective warning marker,	Test plug,
with high-voltage symbol, black, for 5 terminal blocks	with 500 mm cable, 2 mm Ø
yellow 2000-115 100 (4x25)	red 210-136 50
Double-deck marker carrier,	Test plug,
pivoting	with 500 mm cable, 2.3 mm Ø
gray 2000-121 50 (2x25)	yellow 210-137 50
WMB Multi marking system,	
10 strips with 10 markers per card, for 3.5 mm terminal block width	
plain 793-3501 5	
Marking strip, plain,	
11 mm wide, 50 m roll	
white 2009-110 1	