XVMC35

illuminated unit - \varnothing 45 - yellow - BA 15d - bulb not included - <= 230 V AC DC



Main

Range of product	Harmony XVM
Product or component type	Indicator bank
Beacon or indicator bank unit ty	pellluminated unit
Component name	XVM
Light source	Orange bulb not included
Bulb type	Flash discharge tube Incandescent with BA 15d base Super bright LED
[Us] rated supply voltage	<= 230 V AC/DC

Complementary

Mounting diameter	45 mm	
Assembly style	Customer assembly	
Power dissipation in W	<= 5 W	
Connections - terminals	Screw terminals: 1 x 0.3251 x 1.5 mm ²	
Marking	CE	
[Ui] rated insulation voltage	250 V conforming to IEC 60947-1	
Nominal voltage limit	0.851.1 Un conforming to IEC 60947-5-1	
[Uimp] rated impulse withstand voltage	4 kV conforming to IEC 60947-1	
Luminance	650 cd/m ²	:
CAD overall width	47 mm	
CAD overall height	65 mm	
CAD overall depth	47 mm	
Product weight	0.04 kg	 -

Environment

Product certifications	CCC
Standards	EN/IEC 60947-1 EN/IEC 60947-5-1
Ambient air temperature for storage	-2570 °C
Ambient air temperature for operation	-1050 °C
IP degree of protection	IP40 in any position except vertical position conforming to IEC 60529 IP42 in vertical position conforming to IEC 60529
Class of protection against electric shock	Class I aluminium tube mounting conforming to IEC 60947-1 Class I aluminium tube mounting conforming to IEC 60947-5-1 Class I aluminium tube mounting conforming to IEC 61140 Class II base mounting conforming to IEC 60947-1 Class II base mounting conforming to IEC 60947-5-1 Class II base mounting conforming to IEC 61140
Protective treatment	TC